



Electrical Specification

ITEMS	SPEC	UNIT
Center Frequency [fo]	2590.0	MHz
Bandwidth [BW]	fo ±100.0 [2490~2690]	MHz
Insertion Loss in BW	1.5	dB max
Ripple in BW	0.5	dB max
Return Loss in BW		dB min
Attenuation <input checked="" type="checkbox"/> Absolute Value <input type="checkbox"/> Relative Value	30.0 dB min. @ fo ± [2170&]	MHz
	20.0 dB min. @ fo ± [2306&]	MHz
	10.0 dB min. @ fo ± [2340&]	
	3.0 dB min. @ fo ± [2740&]	MHz
	15.0 dB min. @ fo ± [2870&]	MHz
Group Delay Variation		ns max
Input Power		W max.
In/Out Impedance	50 Ω	
Operation Temperature Range	-40°C to +85°C	

Mechanical Specification




Plot Data



Recommended PC Board Pattern

Soldering Condition



Measuring point of temperature : IN-OUT Terminals of The Device

Reflow Soldering : Both Convection and Infrared Rays, Hot Air and Hot Plate

Reflow standard condition	TP0 (°C)	TP1 (°C)	T1 (s)	TP2 (°C)	T2 (s)	TP3 (°C)
Sn-3Ag-0.5 solder	245±/5	220	30 to 60	—	—	150 to 180
Test condition of reflow heat resistance	260+5/-0	240	20	220	70	150 to 180